



## TECHNICAL DATA/SPECIFICATION

**MODEL:** CRE-2110 ELITE CURVE  
**RATED LOAD:** 400 LBS, ONE PASSENGER  
**POWER SOURCE:** 24 VOLT DC COMPRISED OF (2) 7 AMP/HR 12 VOLT SEALED BATTERIES  
 110 VOLT AC 1.5 AMP, 24 VOLT DC 2 AMP CONTINUOUS MONITORING CHARGER.  
**DRIVE:** 24 VOLT DC DIRECT DRIVE GEAR-MOTOR, 2 POLE RATED .68 HP, 58:1 RIGHT ANGLE SELF LOCKING GEARBOX, 41.5 RPM NO LOAD RPM OUTPUT SPEED.  
**SUSPENSION:** RACK & PINION - INTEGRATED 8DP GEAR RACK ON RAIL WITH A SPUR GEAR ON THE OUTPUT SHAFT OF THE GEAR BOX.  
**BRAKING:** DYNAMIC MOTOR BRAKING THROUGH THE MOTOR CONTROLLER, SELF LOCKING WORM GEAR, AND ELECTRO-MECHANICAL MOTOR BRAKE.  
**CONTROLS:** CONTINUOUS PRESSURE ROCKER SWITCH LOCATED ON THE ARM REST AND WALL MOUNTED CALL/SEND CONTROLS LOCATED AT BOTH THE TOP AND BOTTOM LANDINGS.  
**ANGLES:** 0 TO 45 DEGREES (SPECIALS UP TO 50 DEGREES) RIGHT OR LEFT HAND ORIENTATIONS.  
**FINAL LIMIT SWITCH STANDARD OPTIONS:**  
 1) KEYED CALL/SEND CONTROLS,  
 2) KEYED CONTROL ON CHAIR,  
 3) COMMERCIAL PACKAGE W/OVERSPEED SAFETY BRAKE.



DIMENSIONS ARE BASED ON 7.5" RAIL TO WALL POSITION

### SIDE VIEWS



DIMENSIONS WITH \* ARE APPROXIMATE. THESE DIMENSIONS MAY VARY BASED ON THE SLOPE, RISER HEIGHT, AND CUSTOM SEAT ADJUSTMENTS MADE FOR THE USER.

1780 Executive Drive  
 Oconomowoc, WI 53066  
 Tel 800-882-8181  
 Fax 262-953-5501  
 www.bruno.com



©Bruno Independent Living Aids, Inc.

**ILS-00904**

**SHEET 1 OF 2**

**REV. 1 (7028)(10/22/2019)(JEB)**

# CRE-2110 TECH DRAWING

